POWER-TROWEL MANUFACTURER	MODEL NUMBERS	ROTOR / PAD DRIVER DIAMETER, INCH	NO OF PAD DRIVERS	GYRO DRIVER ATTACHEMENT
HUSQVARNA	CRT36	36/14	8	Attachment A
	CRT36 (Inner bolt hole spacing)	36/14	8	Attachment A
	CRT46KHN	46/14	8	Attachment B
	CRT4825K	48/14	8	Attachment B
	CRT48	48/14	10	Attachment B
	CRT48 (Inner bolt hole spacing)	48/14	10	Attachment B
	CRT 60 X	59 / 14	12	Attachment D
Atlas Copco	BG740	36/14	8	Attachment A
	BG910	46/14	10	Attachment B
	BG920	46/14	10	Attachment B
Allen	Edgers 900 / MP225 / MP235	36/14	8	Attachment A
	Pro 900 n-o/MP205/MP215	36/14	-8	Attachment A
	HP100/HP200/MP305/MP315/ Pro 1200 (non-overlap)/SP400/SP450	46/14	8	Attachment B
	HD530/HDX600/Pro1200/MSP415/425/450/ 455/470/430/435/440/445/460/SP400B/SP425	46/14	10	Attachment B
Wacker Neuson	CRT36	36/14	8	Attachment A
	CRT36 (Inner bolt hole spacing)	36/14	8	Attachment A
	CRT46KHN	46/14	8	Attachment B
	CRT4825K	48/14	8	Attachment B
	CRT48	48/14	10	Attachment B
	CRT48 (Inner bolt hole spacing)	48/14	10	Attachment B
	CRT 60 X	59 / 14	12	Attachment D
Whitman / Multiquip	JTN / JWN	36/14	8	Attachment A
	HTH/HHN/HTX/HHX/HTN	48/14	10	Attachment B
	HTN (4-bladed model)	48/14	8	Attachment B
	HTXD6i/HTXG6DF/HTX6H	48/14	12	Attachment C
	STH/STX	60/14	12	Attachment C