

# Husqvarna S 36

S 36 is a very powerful single-phase HEPA dust extractor to match the grinding machines Husqvarna PG 530 (1-phase), PG 450, PG 400 and PG 280 as well as small to mid size scarifiers, grinders, shot blasters and handheld power tools. This professional dust extractor is designed to meet strict demands. Three large, commercial-grade vacuum motors provide plenty of power. Equipped with three independently tested and certified HEPA H13 filters and a massive cone-shaped pre-filter with over 4.5 m<sup>2</sup> of media. This results in superior dust collection, even of fine sanding and gypsum dust. Features include Jet Pulse pre-filter cleaning, hour counter and vacuum meter for filter control. The non-marking wheels are puncture free and lock at the front. The Longopac® bag hose system ensures simple, dust-free bag changes.

- Phases **1~**
- Air Flow **600 m<sup>3</sup>/h**
- Rated input **3.6 kW**  
power
- Weight **63 kg**

Article number : DUST EXTRACTOR S 36

230 V | 1-ph | EU - 967 66 38-07



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm). +



### Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.

### Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



### Easy to transport

The welded frame enables easy transportation by resting the machine on the frame.



- High Efficiency Particulate Air filter
- Easy-to-read airflow monitoring
- Clean and simple bag change

- For demanding industrial applications
- Control

## SPECIFICATIONS



### Motor

Phases	<b>1~</b>
Voltage	<b>230 V</b>
Rated current	<b>15,7 A</b>
Max. vacuum	<b>220 mbar</b>
Rated input power	<b>3.6 kW</b>



### Dimensions

Product size height	<b>1500 mm</b>
Product size length	<b>830 mm</b>
Product size width	<b>620 mm</b>
Weight	<b>63 kg</b>

## Specifications

Air Flow	<b>600 m<sup>3</sup>/h</b>
HEPA filters 99.99% at 0.3 microns	<b>3</b>
Max. vacuum	<b>220 mbar</b>
Water lift	<b>90 in</b>